

**The Imagination Machine**

**APF BASIC**  
Language Reference Manual

**APF**  
electronics inc.



# The Imagination Machine

## APP BASIC

This version of the popular BASIC computer language has been specifically designed and written for the APP Imagination Machine. Special features of this language include:

- Three octave music system
- High and low resolution color graphics
- Hand control input commands
- Four place fixed decimal arithmetic with 12 digit accuracy

The information in this manual is organized and presented for use by experienced programmers. For an introduction to BASIC programming, we suggest BASIC Tutor™ — an interactive teaching system available for your APP personal computer.

**INFOINDEX**

<b>CHAPTER 1 KEYBOARD AND HAND CONTROLS</b>	<b>PAGE 6</b>
<b>CHAPTER 2 GENERAL</b>	<b>PAGE 7</b>
NUMBER VARIABLES	RULES OF PRECEDENCE
LETTER VARIABLES	LINE LENGTH, SPACING
VARIABLE NAMES	MULTIPLE STATEMENTS
ALGEBRAIC OPERATORS	MAXIMUM LINE NUMBER
RELATIONAL AND LOGICAL OPERATORS	
<b>CHAPTER 3 COMMANDS</b>	<b>PAGE 8</b>
EDIT	
LIST	
LIST 100	
LIST 100:	
LIST 100-5	
RUN	
<b>CHAPTER 4 PROGRAM STATEMENTS</b>	<b>PAGE 9</b>
CALL	
DATA \$10 BILL	
DIM ASS(10) B\$(4,12) CS \$)	
END	PAGE 9
FOR A=10 TO C	
FOR A=10 TO 1 STEP-1	
GOSUB 100	
GOTO 100	
IF A=B THEN 300	
IF A<B THEN GOSUB 2000	
IF A>B THEN PRINT "EQUAL" END	
INPUT A	
INPUT A B	
INPUT "AMOUNT" A	
LET A=5 or A=5	PAGE 10
ON A GOSUB 1000 1200 1500 2000	
ON A GOTO 10 20 30	
POKE TME 1	
PRINT A	
PRINT A,B	
PRINT A,B,C	
PRINT A TAB(10)B	
PRINT A SPC(10)B	
PRINT HELLO	
PRINT USING "####.##" A	
PRINT USING "#####.### TOTAL IS ####.##" A,B	
PRINT USING A1 B	
PRINT USING 100 A	
READ A,B	
RESTORE	
RETURN	
STOP	
	PAGE 11

<b>CHAPTER 5 ARITHMETIC FUNCTIONS</b>	<b>PAGE 11</b>
ABS(X)	
INT(X)	
PEEK(X)	
RND(X)	
SGN(X)	
<b>CHAPTER 6 STRING FUNCTIONS</b>	<b>PAGE 12</b>
ASC(A\$)	
CHR(N)	
KEYS(X)	
LEN(A\$)	
ADDRESSING CHARACTERS IN A STRING	
<b>CHAPTER 7 MUSIC</b>	<b>PAGE 13</b>
<b>CHAPTER 8 GRAPHICS (64 x 32)</b>	<b>PAGE 14</b>
COLOR	
SHAPE	
PLOT 10,8	
HUM 10,20,8	
VUM 8,12,10	
CLEAR SCREEN	
EXAMINE SCREEN LOCATION	
REVERSE VIDEO (BLACK/ORANGE)	
REVERSE VIDEO (GREEN/GREEN)	
LOCATE CURSOR	
POSITION CURSOR	
<b>CHAPTER 9 GRAPHICS (128 x 192)</b>	<b>PAGE 15</b>
MODE SELECT	
MEMORY MAPS	
DEFINE SHAPES	
PLOT SHAPES	
EXAMPLE	
<b>CHAPTER 10 TAPE</b>	<b>PAGE 19</b>
SAVING PROGRAMS	
LOADING TAPES	
AUDIO RECORDING	
AUDIO SHUTOFF	
MOTOR START/STOP	
<b>APPENDIX</b>	<b>PAGE 20</b>
A. RESERVED WORDS	
B. ASCII CODES	
C. MACHINE LANGUAGE ACCESS	
D. ERROR MESSAGES	

## CHAPTER 1 KEYBOARD AND HAND CONTROLS

Study the keyboard carefully. Most of the keyboard is like a standard typewriter with unusual special keys. In addition to the special keys the Imagination Machine also has two rows of control keywords across the top of the keyboard. Use of the special keys is described in the section below.



### **ESC**

When ESC is pressed a ! appears on the screen.

### **CTRL**

The CTRL key allows you to use the control keywords printed above the top row of keys. The two rows of control keywords correspond to the top two rows of keys. To print GO TO on the screen hold down the CTRL key and press the G key. To print CLOAD on the screen hold down the CTRL key and press the RETURN key.

### **SHIFT**

Since the computer has no lower case letters the SHIFT keys are only used to print the symbols on the upper half of the number keys and wherever shown on other keys.

### **HERE IS**

Is not used in the current version of APP BASIC.

### **LINE FEED**

Is not used in the current version of APP BASIC.

### **RETURN**

The RETURN key acts like the carriage return on a typewriter. It is also used to tell the computer when you are through entering. When this key is pressed the computer will look at what you have typed and decide what to do with it.

### **RUB OUT**

The RUBOUT key is used to back space and erase one character at a time.

### **REPT**

The REPT repeat key is used to make any other key print continuously on the screen as long as you hold down both keys up to the maximum line length of 120 characters.

### **BRK**

The BRK (break) key causes your program to stop running and return to user input or control mode. It does not function during an input statement or while saving and loading on tape.

### **HAND CONTROLS**

There are two hand controllers attached to the MP 1000. One is marked with an L for left and the other with an R for right. They can be accessed with a key 5 function of 12.1.



## CHAPTER 3 COMMANDS

### EDIT

The EDIT statement is used to change a portion of a line in your program. It must be followed by the line number you want to change and the ESC key. Then type the section of the statement you want to change. Press the ESC key again and then the new characters.

EXAMPLE: EDIT 14 ESC X ESC Y RETURN

X is line # to be edited

X is text to be deleted

Y is text to replace X

EXAMPLE: 100 INPUT AS PRINT INS

200 IF INS = NOT THEN 1000

300 IF INS = YES THEN 100

EDIT 100 AS INS

EDIT 200 IT

EDIT 300 IR RETURN

L1ST

100 INPUT INS PRINTING

200 IF INS = NO THEN 1000

300 IF INS = YES THEN RETURN

### L1ST

Lists all lines in your program

### L1ST 100

Lists line 100 of program

### L1ST 100..

Lists from line 100 to end of program

### L1ST 100..5

Lists five lines of your program beginning with line number 100

### RUN

Sets all variables to zero Execution then begins with the first line in your program

## CHAPTER 4 PROGRAM STATEMENTS

### CALL

Transfers program execution to a machine language routine written in M6800 object code.

EXAMPLE: CALL 17046

This call branches your program to a special sub routine that begins at location 17046. This particular sub-routine will clear the TV screen. When a 6800 RTS instruction occurs, return will be to the next basic statement.

### DATA \$, @, !, ##

Saves data to be accessed by READ statements. Data items will be read sequentially. Items may be numbers or characters but not expressions. Each data item must be separated by a comma.

### DIM

Reserves memory for strings, lists of strings, or tables of numbers.

EXAMPLE: DIM A\$(10) B\$4(12) C(5)

This example reserves memory for an 11 character string (A\$), 5 strings of 12 characters each (B\$) and a table of numbers that is 5 rows by 9 columns (C). Maximum string length is 100 characters. At(0))

**END**

Stops program and returns control to the console

**FOR A=B TO C**

Combines with a **NEXT** statement to form a loop. Variable A begins with the value of B and increments to the value of C.

**FOR A=10 TO 1 STEP-1**

Combines with a **NEXT** statement to count from 10 to 1. Note: if step value is not given, it is assumed to be 1.

**EXAMPLE 10 FOR A = 10 to 1 STEP-1**

```
20 PRINT A  
30 NEXT A
```

**GOSUB 100**

Calls a BASIC subroutine located at line 100

**GOTO 100**

Transfers program to line 100

**IF A=B THEN 300**

Transfers program to line 300 if A equals B. If A is not equal to B the rest of the line is not read by the computer and the program transfers to the next numbered line. Any comparison can be used. Such as:

- = equal
- <> not equal
- > greater than
- < less than
- >= greater than or equal
- <= less than or equal

**IF A<B THEN GOSUB 2000**

Transfers program to the subroutine at 2000 if A is less than B. The value of A/B is compared to the value of B. Alphabetically Numerals come before letters alphabetically.

**IF A = B THEN PRINT "EQUAL" END**

Prints the word EQUAL and ends the program if A and B are not equal. If A equals B then the next line of the program is executed.

**INPUT A**

Reads data from the keyboard. A question mark is displayed to indicate that the computer is waiting for a response. Separate multiple input items with a comma. Command is only terminated after a return key is pressed.

**EXAMPLE INPUT A,B**

The user must respond with two numbers separate by commas. If only one input is given, then computer automatically asks for second one (B).

**INPUT A\$B**

The user must enter a character string comma and a number

**INPUT "AMOUNT", A**

Prints the word AMOUNT followed by a question mark and waits for the user to type in a number.

**NOTE:** If a number is being requested and the user responds with a group of characters beginning with a letter, then the computer accepts the input as if he types a \$  
If the user types a group of characters beginning with one or more numerals, the computer accepts those numerals as the number.

**LET A=5 or A=5**

Sets the variable A equal to the constant 5. The word LET is optional and A=5 also works. The constant 5 can be replaced by an arithmetic expression.

**EXAMPLE A = 3+B+C = 4**

B = 3+B+C A = 12\*C

This example is equivalent to B = 3+(B/C) = (A+2)\*C

**ON A GOSUB 1000 1200 1500 2000**

Calls one of a list of subroutines depending on the value of A. If A equals one, GOSUB 1000 results. If A equals two, GOSUB 1200 results, and if A equals three, GOSUB 1500 results. If A equals any other value, then GOSUB 2000 results.

**ON A GOTO 10 20 30**

Jumps to one of a list of lines depending on the value of A. If A equals one, GOTO 10 results and if A equals two, GOTO 20 results. Any other value results in a GOTO 30.

**POKE 784,1**

Places the number 1 in memory location 784. This POKE displays the letter A in the middle of your screen. Any memory location can be poked as long as it is between 0 and 65,536. The value poked must be a positive integer from 0 to 255. If greater than 255, modulo 256 is performed.

**PRINT A**

Prints the value of A.

**PRINT A,B**

Prints the values of A and B in separate columns. Columns are automatically 8 characters wide (if A is column 1, B is printed in column 9).

**PRINT A,B**

Prints the values of A and B with no spaces between them.

**PRINT A TAB(10)B**

Prints the value of A, spaces ten characters from the left margin, and prints the value of B.

**PRINT A SPC(10)B**

Prints the value of A, spaces ten characters from the last character in A, and prints the value of B.

**PRINT "HELLO"**

Prints HELLO.

**PRINT USING "\$###.##" A**

Prints the value of A with a leading dollar sign and two decimal places - \$129.90  
\$100.01 \$0.02 etc. You must use as many pound signs (#) as there are digits in the value of A.

**PRINT USING "\*\*\*\*\* TOTAL IS \*\*\*" A,B**

Replaces the pound signs (#) with the characters in A,B and the value of B - SATURDAY TOTAL IS 120 OODOMSDAY TOTAL IS 27 TOTAL IS 205 etc

**PRINT USING A\\$ B**

Prints the value of B using the characters in A\\$ as the format. The format string is contained in the string variable A\$.

### PRINT USING 100A

Prints the value of A, using the data in line 100 as the format. Line 100 must begin with a colon and quotes are not required.

```
100 :EE:EEE  
100 EEE:EEE:  
100 LAST QUOTE: EEE:
```

### READ A,B\$

Reads data into the specified variable from DATA statement.

EXAMPLE: 100 DATA 37 BILL SAM \$

```
200 READ A,B$  
300 READ C,D,E,F$  
310 DATA 42 THE
```

Note that DATA statements can be placed after the READ statements.

### RESTORE

Resets the data pointer so that the next READ statement begins with the first DATA statement in the program.

EXAMPLE: 100 DATA 37 BILL B SAM

```
200 READ A,B$  
300 RESTORE  
400 READ C,D$
```

In this example C will be assigned the value 37.

### RETURN

Returns from the subroutine to the statement following the OSUB.

### STOP

Stops the program.

## CHAPTER 5 ARITHMETIC FUNCTIONS

All functions are written of the form:

NAME(X)

Name is the function mnemonic. No spaces are allowed between the name and the left parenthesis.

X is the operand and can be a constant, expression or function.

ABS(X) – returns absolute value of x.

$$ABS(-1.2) = 1.2$$

$$ABS(0) = 0$$

$$ABS(1.45) = 1.45$$

INT(X) – returns integer portion of X. Fractional portion of x is truncated.

$$INT(12.34) = 12$$

PEEK(X) – returns decimal value stored in memory location X. X is a decimal address.

EXAMPLE: A=PEEK(41452)

In this example the value of memory location 41452 is placed in A. If it is @ then CSAVE will place the TV image at the beginning of your tape.

RND(X) random number between 0 and .9999

SQRT(X) 1 if x>0 -1 if x<0 0 if x=0

## CHAPTER 6 STRING FUNCTIONS

**ASC(AS)** Returns ASCII Code of the first character in AS.

Ex: PRINT ASC( A )

65

This is decimal ASCII code for letter A.

**CHR( N )** Produces string of one character length whose ASCII code is N.

Ex: PRINT CHR(31)

—

This is the letter whose ASCII code is decimal 31.

**LEN(AS)** Returns # of characters (Length) in AS.

Ex: DIM AS(10)

AS = ABC

PRINT LEN( AS )

3

Length is 3

**KEY\$(0)** Checks the typewriter keyboard. If no key is pressed, AS= " " if key is pressed.

AS = C where C is the character typed.

EXAMPLE: 10 AS=KEY\$(0) IF AS=" " THEN 10

20 PRINT AS

Line 10 is asking if any key on the keyboard is pressed. If no, it loops back to the beginning of line 10 and asks again. If a key is pressed, the program drops through to line 20 and prints that key on the screen.

**AS=KEY\$(1)**

Reads the left hand control. If no key is pressed, AS= " " if key d to f is pressed. AS = n where n is the number of the key if the knob is moved. AS = d if the direction (N S E or W) if CL is pressed. AS = ? if either EN or the FIRE button is pressed. AS= !

**AS=KEY\$(1)**

Reads the right hand control in the same manner as described above.

### ADDRESSING CHARACTERS IN A STRING

Since strings are dimensioned as arrays, it is possible to address any character or group of characters in a string.

EXAMPLE:

DIM AS(9) BS(1)

AS = ABCDEF GHJ

PRINT AS

PRINT AS(4)

BS = AS(3) PRINT BS

This prints ABCDEF GHJ

This prints EFGHJ

This prints DE

## CHAPTER 7 MUSIC

Using the MUSIC command you can write and play music on your computer using numbers. The numbers 1 through 7 play the musical scale.



To play one octave higher, place a multiply sign (\*) in front of the number, and to play one octave lower, place a divide (/) sign in front of the number.

/1 /3 /5 /7 2 4 6 +1 +3 +5 +7  
/2 /4 /6 1 3 5 7 +2 +4 +6



You can also play sharps and flats by typing a + or - sign in front of the note. The number zero (0) is used to hold the previous note. Leaving a space between numbers creates a pause in the music.

EXAMPLE: MUSIC 32123000

MUSIC 321230000000

If the music plays too quickly you can slow it down by placing a 0 between each note:

MUSIC 302010203030

Spaces create a different sound:

MUSIC 3 2 1 2 3 3 3

If you want to use the same sequence of notes over and over you can assign them to a variable:

MUSIC A,B,

EXAMPLE: 10 For I=1 to 10

DO Music /1/2/3/4/5/6/71234567\*\*1=2\*3\*4\*5\*6\*7

DO Next 1

EXAMPLE: Let's try a song:

MUSIC 32123 3 3 2 2 2 3 5 5 32123 3 3 3 2 2 3 2 1

EXAMPLE: Using A,B,

A:= 5552332

B:= 74665

MUSIC A,B,

The low resolution graphics mode divides the screen into 512 cursor size rectangles: 32 columns wide by 16 rows high (32 x 16). These are the same 512 blocks used to show alphanumerics and therefore this mode allows mixing of alphanumerics and color graphics on the screen.

### COLOR

Any cursor position can be any one of eight colors at any time by assigning it a color number from 0 to 7. Setting COLOR = expression determines the color to be used in the next line or plot command. Expression can be a constant or expression. Modulo arithmetic is performed so the expression can be greater than 7.


0 - Dark Green	4 - White
1 - Yellow	5 - Light Green
2 - Blue	6 - Purple
3 - Red	7 - Orange

This means you can have eight different colors on the screen at the same time.

### SHAPE

To get higher resolution each cursor position can be divided into four cells. By selecting the appropriate shapes you can draw a picture with much higher resolution (64 x 32).

The shape table shows the number for each cursor shape:



Shape is set equal to a constant or expression. Its value is used in the next plot or line command modulo 15 arithmetic is performed so shape can be greater than 15.

Since only one color can be assigned to a cursor position the cells that are lit will all be the same color and the remaining cells will be black.


SHAPE	6	BLACK	YELLOW
COLOR	4	YELLOW	BLACK

### PLOT

To select the X and Y position on the screen where you want the shape to appear use the PLOT command.

## PLOT 10,8

Means place the shape in the 10th column in the 8th row



To place shape 6 on the screen in yellow and black in the position X = 10, Y = 8 the command would be

60 COLOR=1 SHAPE=6 PLOT10,8

## LINE

To draw a horizontal line of the selected shape use the HLIN command and specify the starting column, the ending column and the row

## HLIN 10-20,8

Means draw a line starting in column 10 ending in column 20 using row 8. The same process is used to draw vertical lines on the screen.

## VLIN 8,12,10

Means draw a vertical line starting in row 8 ending in row 12 using column 10

**NOTE** If you plot a shape on top of another shape the second shape is added to the first shape it does not replace it. The new shape takes on the new color  
Plotting a 0 on top of a 6 gives you a 15

## EXAMPLE 10 SHAPE=15

```
20 FOR I=0 TO 7  
30 COLOR=1  
40 HLIN 1,31-I,1  
50 HLIN 1,31-I,15-I  
60 VLIN 1,15-I,1  
70 VLIN 1,15-I,31-I  
80 NEXT I  
90 GOTO 90
```

## CLEAR SCREEN

To clear the screen use CALL 17046

## EXAMINE SCREEN LOCATION

A = PEEK(512 + Y\*32 + X)

### EXAMPLE

PRINT PEEK(512 + 10\*32 + 16)

This prints the contents of the 16th position of the 10th row. The numbers 512 and 32 are always used as shown. The other two numbers determine the X and Y coordinate of the screen.

If A > 127 the location contains a shape ( etc.)

If A < = 127 the location contains a character (A, B, C, etc.)

0 ≤ A ≤ 63 light green character on dark green

A = CHARACTER

A =   
CHARACTER CODE (APPENDIX A)

64 ≤ A ≤ 127 dark green character on light green

A = CHARACTER = 64

A =   
CHARACTER CODE (APPENDIX A)

128 ≤ A ≤ 195 shape

A = 128 + COLOR\*16 + SHAPE

A =   
COLOR      SHAPE

## REVERSE VIDEO (BLACK/ORANGE)

POKE 8193 60

Changes color of reverse video characters from dark green on light green to black on orange. This does not affect letters in standard video: light green on dark green.

## REVERSE VIDEO (GREEN/GREEN)

POKE 8193 62

Restores standard video. Use after POKE 8193 60

## LOCATE CURSOR

A = Peek(40960Y\*256 + PEEx40961)

Places in A the position of the cursor

A = ROW\*32 + COLUMN + 612

A =   
ROW      COLUMN

## POSITION CURSOR

Position cursor by setting A as shown and poking two locations. To position cursor in 22,7

- L=7
- P=22
- A=L\*32 + P + 612
- POKE 40960,A/256
- POKE 40961,A.INT(A/256)\*256

## CHAPTER 9 GRAPHICS (128x192)

Graphics mode (128x192) - There is a high resolution graphics mode which has the following features:

1. 128x192 resolution
2. 2 color sets each with 4 colors so there can be a total of 8 colors on the screen at once

### NODE SELECT

Enter the graphics mode with:

POKE \$193,60

POKE \$194,156

Return to the (64x32) graphic mode with:


POKE \$193,52

POKE \$194,30

When the computer is in this mode there is no alphanumeric capability. Therefore, pressing keys or the keyboard will not produce letters on the screen but will cause the computer to take a directed action.


### MEMORY MAPS

Two memory areas are used. The screen map occupies memory locations 0 to 383 and the shape table occupies locations 312 to 1023.



The TV screen is divided into 384 object boxes (12 rows by 32 columns). Each box may contain any one of 32 special shapes.

These shapes are stored in the shape table and numbered 0 to 31.



The shape table describes each of the 32 shapes that can be displayed. Each shape is composed of 16 bytes, one byte for each horizontal row of data in the shape.

## DEFINE SHAPES

In this graphic's mode each shape to be plotted on the screen is 4 dots wide and 16 dots high.

Each horizontal row of four dots is set with a POKE instruction. For example, this POKE sets the top row of dots in shape number one to the colors C1, C2, C3, and C4  
POKE 512 C1\*16+C2\*16+C3\*4+C4

Each color number is between 0 and 3 depending on the color selected. The color tables are in the next section.

The example at the end of this section shows how up to 99 shapes can be created with similar POKE instructions.

## PLOT SHAPES

After the shapes have been created in the shape table they can be plotted on the screen.

The format for each byte in the screen map is:



## COLOR TABLE

If color table select = 0

- 0 GREEN
- 1 YELLOW
- 2 BLUE
- 3 RED

If color table select = 1

- 0 WHITE
- 1 AQUA
- 2 PURPLE
- 3 ORANGE

NOTE: The color table is selected in the screen map and the specific color in the table is included in the shape definition.

## EXAMPLE

```
100 L=6 REM LINES ARE 9 TO 11
110 P=10 REM POSITIONS ARE 9 TO 31
120 S=13 REM SHAPES ARE 9 TO 31
130 T=0 REM COLOR TABLES ARE 0 OR 1
140 DATA 0 0 1 1 REM A SHAPE IS 4 DOTS ACROSS
150 DATA 0 0 1 1 REM BY 16 DOTS DOWN
160 DATA 0 1 1 2 REM
170 DATA 0 1 1 2 REM EACH DOT IS ONE OF FOUR
180 DATA 1 1 2 2 REM COLORS
190 DATA 1 1 2 2 REM
200 DATA 1 2 2 3 REM EACH COLOR IS NUMBERED 0 TO 3
210 DATA 1 2 2 3
220 DATA 2 2 3 3
230 DATA 2 2 3 3
240 DATA 2 3 3 0
250 DATA 2 3 3 0
260 DATA 3 3 0 0
270 DATA 3 3 0 0
280 DATA 3 0 0 1
290 DATA 3 0 0 1
300 REM
310 REM SET UP THE SHAPE
320 REM
330 FOR I=9 TO 15
```

```
240 REM AD A B C D
250 POKE 512 +$1'16 +LA784 +B'16 +C74 +D
260 LET X T I
270 REM
280 REM PLACE THE SHAPE ON THE SCREEN USING
290 REM THE CHOSEN COLOR TABLE
400 REM
410 POKE L'32 +P S +T#4.
```

## CHAPTER 10 TAPE

### Tape Operation

The tape system is specially designed for the Imagination Machine. The key features are:

- 1 Dual track tapes are used. One for standard audio recording or playback, and the other for digital recording or playback.
- 2 Microphone jack built in for audio recording. Any standard cassette microphone may be used.
- 3 Separate speaker built in for audio playback. Volume control is included.
- 4 Semi-automatic computer control. Record or playback of either audio or digital is under computer control. Fast forward and rewind are manually operated.
- 5 High speed digital transfer rate—approximately 1000 bits per second.
- 6 Tape counter included to allow manual location (thru fast forward or rewind) of a desired section of tape.

### SAVING PROGRAMS

CSAVE is used to save program memory. It is not necessary to press the record button on the tape deck since that is used only to record audio. Do not delay more than 5 seconds when pressing the play/save button and the return key. For an 8K system CSAVE takes about 45 seconds.

During a CSAVE all keyboard functions are inoperative. CSAVE will save the entire amount of random access memory.

### Saving 512 Block for Screen

In addition to the program memory, CSAVE first saves a block of 512 bytes. This will be placed on the screen first when loading so pictures or messages can be stored. There are 2 possible blocks that can be saved. The selected one is determined by the contents of memory location 41452.

If 41452 = 0 then locations 512-1023 (screen memory) are saved.

If 41452 = 265 then locations 0-511 (scratch memory) are saved.

### Saving Program Data

Since CSAVE always saves all memory then all dimensioned variables are also saved on tape. This can be used to save and revo data. Simply use a goto statement to start the program after loading (run automatically clears all variables).

Note: After a reset is pressed one RUN command is always necessary to initialize certain system constants. Therefore we recommend that if you want to use a tape with data do the following sequence:

1 CLOAD	
RUN	1st RUN after repeat
Follow instructions to load	
When OK appears	
Type GOTO x where x is first statement of loaded program	

### LOADING TAPES

CLOAD is the command for loading tapes. The first 612 bytes of the tape are always put to screen memory. After that the next 8K bytes are read to program memory. At the end of loading there is a check sum to indicate all data is read correctly. If it was the word OK appears on the left side of the screen and the cursor returns. If anything except OK appears it was a bad load and the tape must be reloaded.

## AUDIO RECORDING

One of the nice features of the Imagination Machine is that you can record your voice or even music on the same tape as your computer program. To do this, plug a microphone into the microphone jack on the body of the keyboard unit and press the record key. Now type in the following statement:

POKE 24578 62

This turns on the motor. Now talk or play music into the microphone. It is being recorded on the audio track of the tape without damaging or changing any programs you may have placed on the program track.

To turn off the motor, type:

POKE 24578 38

## AUDIO SHUTOFF

To stop the voice track on a program tape from playing through the speaker, type:

POKE 24578 54

## MOTOR START/STOP

To start the cassette tape motor and align to the audio track, type:

POKE 24578 62

To stop the cassette tape motor, type:

POKE 24578 38

## APPENDIX A

### RESERVED WORDS

The following words can not be used as or contained variable names

ABS	MUSIC
ASC	NEXT
CALL	ON
CHR\$	OPEN
CLOND	PEEK
COLOR	PLOT
CSAVE	POKE
DATA	PRINT
DIM	READ
END	RESTORE
FOR	RETURN
GOSUB	RND
GOTO	RUN
HUIN	SON
IF	SHAPE
INPUT	SPC
INT	STEP
KEYS	STOP
LEN	TAB
LET	THEN
LST	TO
POKE	USING
PRINT	VJIN

## APPENDIX B

### ASCII CODES AND TOKENS

The following are codes used to place alphanumerics on the screen.

Decimal	Will Appear	Decimal	Will Appear
0	0	37	~
1	1	38	!
2	2	39	"
3	3	40	#
4	4	41	\$
5	5	42	%
6	6	43	&
7	7	44	*
8	8	45	(
9	9	46	)
10	:	47	,
11	,	48	-
12	-	49	=
13	+	50	<
14	-	51	>
15	<	52	=
16	>	53	;
17	=	54	:
18	;	55	;
19	:	56	;
20	;	57	;
21	;	58	;
22	;	59	;
23	;	60	;
24	;	61	;
25	;	62	;
26	;	63	;
27	;	64	;
28	;	65	;
29	;	66	;
30	;	67	;
31	;	68	;

## APPENDIX C

### MACHINE LANGUAGE REFERENCE

The Imagination Machine contains a machine language monitor. You can use the monitor to create, display, change, and execute machine language programs. To use this appendix, you must be able to write programs in 6800 machine language. You must also have a working knowledge of hexadecimal notation.

#### CALL 28072

This BASIC statement takes you out of BASIC. You are now talking to the Imagination Machine Monitor. The Monitor puts a ":" at the beginning of each line on the screen. When you see the ":" you can enter one of the three monitor commands:

G nnn where nnn is a hexadecimal address

G nnn where nnn is a hexadecimal address

M nnn where nnn is a hexadecimal address

### D nnnn - DISPLAY MEMORY

This command will display the 16 bytes of memory beginning at address nnnn. To display the next 16 bytes, press the "T" key. To end the command, press the RETURN key.

Example : D 993C

- 9B 9C 20 60 B8 A0 B8 BD 9A B8 C6
- A0 9C 7E 9A 20 7C A0
- 9B 4C AA 20 04 B8 04 CE AD AA 9C
- 69 00 09 8C B0 9C 26 {Return}

### G nnnn - GOTO MEMORY ADDRESS

This command acts much like the BASIC GOTO statement except the value NNNNN is a four digit hexadecimal memory address. The computer immediately begins executing the machine language program at that address.

G 8894

Address 8894 is the start of the Imagination Machine's BASIC. This is how you enter BASIC. If you had a BASIC program in memory when you called the monitor, it should still be there.

### M nnnn - MODIFY MEMORY

This command immediately displays the contents at memory address nnnn. You can do one of four things:

- reply with the "T" key and the command proceeds by displaying the next position in memory.
- reply with "T" key and the command proceeds to display the previous memory position.
- reply with the RETURN key and the command is ended.
- reply with a two-digit hexadecimal number and the RETURN key and the command stores this new number in the current memory position. Then you can press Return, or T with the results as above.

If the M command cannot change the memory location, it will respond with a "?" .

## APPENDIX O

### ERROR MESSAGES

The following is a list of error messages. If they occur during a program statement, the statement number is well as the message is displayed.

#### ARITHMETIC OVERFLOW

The result of a computation is greater than 999999999.9999. This problem can be eliminated by using the IF statement to test and limit the sizes of the variables in the equation before doing the computation.

#### DIMENSION

Something is wrong in Dimension Statement (size is zero or greater than 20, etc.).

#### DIVISION BY ZERO

The result of dividing by zero is undefined. The computer cannot proceed. This problem can be prevented by checking the value of a divisor with an IF statement before doing the division.

#### EXPRESSION

The expression is not properly formed. Examples are PRINT PECK, 123 — parentheses not set around expression of a function. PRINT 234\*30 — missing an open parenthesis. PRINT 1 ← 3 — improper operator symbol in an expression.

#### EXPRESSION MISSING

An expression is expected to be located in a statement but is not found.

Example      A = (Return Key)

For H =

## **EXPRESSION TOO LONG**

You did nothing wrong. All computer languages have limits, and you just ran up against one of ours. This will occur if an expression has more than 8 nested brackets or parentheses.

## **FOR - NEXT**

A NEXT statement was executed when no FOR statement had been instituted. Check your program. You have forgotten to supply the FOR parameter or the logic of your program is incorrect. Somehow you branched to a NEXT sentence without first going through its FOR statement. Fix the logic of your program before continuing.

Example: 10 next I  
RUN

## **IF - THEN**

The comparison in the IF statement is wrong. For example, IF A>B THEN 100. Fix the statement before running the program.

## **ILLEGAL MASK SIZE**

The format defined for a PRINT USING statement is incorrect. For example there may be more than 9 "0" 's to the left of the decimal place, or more than 4 to the right. Correct the PRINT USING format, called a mask, before running the program.

## **ILLEGAL VARIABLE**

This is a catchall error message when the interpreter finds something wrong with a variable. Some examples are:

A variable name starts with an illegal symbol — i.e., a number (1A-3). You have used more than 36 variable names. You used a dimensioned variable name that was not dimensioned.

## **MEMORY FULL**

You ran out of memory. This will usually appear in a DIM Statement. If so, then reduce the allocation in a DIM statement or shorten your program.

Memory storage is as follows:

1. A numeric variable takes 2 Bytes. A dimensioned numeric array takes 2 Bytes for each element. Ex - DIM H(1365) takes 7\*365 Bytes.
2. Each line takes 2 Bytes for a line + plus 1 Byte for an end of line symbol.
3. All keywords (i.e. - PRINT, FOR, etc.) take 1 Byte.
4. Actual allowable user storage is 7166 Bytes.

A second reason for Memory Full can be due to your program's continuous execution of a FOR statement with no NEXT statement, or continuously executing a GOSUB with a RETURN.

## **NO - GOSUB**

A RETURN statement was executed without a GOSUB having been executed. You have a logic error in your program. Make sure you do not use a GOTO or fall into a Subroutine. Fix the problem before running the program.

## **NO LINE # - REFERENCED**

You are trying to GOTO a line number which doesn't exist in your program. Correct the statement before running your program again.

## **PRINT DELIMETER**

There is an error in your PRINT statement. Check to see that each of the items being printed are separated by a comma or semi-colon. Correct the statement before running your program.

## **QUOTE MISSING**

The right quote in a String Constant is missing. Correct the statement before running the program again.

## **READ – DATA**

Either you have executed a READ statement when there is no DATA statement, or there is an error in the DATA statement. If there is an error in the DATA statement, correct it before running the program again.

If you are executing a READ statement, then either you forgot to include a DATA statement or you have tried to READ more variables than you have data in DATA statements. Make sure you have supplied all of the data in the DATA statements, or that you haven't executed a READ statement more times than you had intended.

## **WHAT**

This is a catchall. It usually means that one of the items in the line should have been a keyword but wasn't recognized as such. Carefully check the line and correct all errors before running the program again.

\* > 999999999.9999

You have a constant which has more than four decimal places or which is greater than 999999999.9999 or less than -999999999.9999. You will have to change your program so that numbers outside of this range are unnecessary.



**APF** electronics inc.

444 Madison Avenue New York, NY 10022

Printed in Hong Kong